

DEMOLITION CRUSHER

Demolition crushers BP series have been specifically designed for primary and secondary demolition needs.

Made in HARDOX 400, naturally resistant to wear and fully rotating, BP series crushers are provided with regenerative circuit for fast jaw opening and closing.

360° rotation gives a precise and quick positioning in every working condition.

- Available for excavators from 12 to 180 Tons.
- Innovative valve system "Pressure relief"
- Auto rubbing rotation valve
- Reversed cylinders to protect the rods
- Speed valves
- Anti-wear body
- Interchangeable teeth
- Interchangeable blades

MODEL	BP12	BP16	BP20	BP22	BP28	BP35	BP45	BP55	BP80	BP100	BP120
OPENING (mm)	595	720	850	930	1105	1390	1510	1650	1855	2000	2205
HEIGHT (mm)	1700	2000	2300	2300	2700	2800	2900	3000	3200	3500	3750
BLADE (mm)	160	160	220	220	220	260	320	320	320	320	320
EXCAVATOR WEIGHT (BUCKET) (T)	12-16	16-22	20-30	22-40	28-50	35-60	45-80	55-85	80-120	100-150	120-180
EXCAVATOR WEIGHT (ARM) (T)	7-10	10-14	13-19	15-22	18-32	22-35	28-40	35-42	50-75	60-90	75-100
WEIGHT (Kg)	1090	1460	1950	2220	2700	3800	4810	5790	7780	10980	12120
CLAMPING TO BLADE (T)	1800	200	230	275	320	330	485	590	735	800	855
CLAMPING TO TIP (T)	70	85	95	110	125	130	145	150	185	230	260