

# ROTATING PULVERISER

Rotating pulverizers series BR are made to complete efficiently and fast all operations of primary and secondary demolition.

Made with best steels Hardox, they have a regenerative circuit for fast jaw opening and closing, hydraulic rotation and interchangeable parts.

The ratio weight/length makes these pulverizers suitable for the highest demolitions made with excavators long arms.

- Available for excavators from 7 to 120 Tons
- Innovative valve system "Pressure relief"
- Auto rubbing rotation valve
- Reversed cylinders to protect the rods
- Speed valves
- Anti-wear body
- Interchangeable teeth
- Interchangeable blades

MODEL	BR7	BR9	BR15	BR18	BR24	BR30	BR38	BR50	BR70	BR90
OPENING (mm)	520	635	700	800	910	1055	1150	1300	1350	1715
LENGTH (mm)	1400	1900	2350	2400	2500	2650	2850	3300	3400	3800
WIDTH (mm)	350	400	460	480	480	510	550	580	620	650
BLADE (mm)	140	160	200	240	240	240	240	240	300	300
EXCAVATOR WEIGHT (BUCKET) (T)	7-10	9-15	15-20	18-26	24-32	30-40	38-55	50-70	70-90	90-120
EXCAVATOR WEIGHT (ARM) (T)	3-5	6-9	10-14	11-16	14-19	18-23	23-32	30-50	45-65	55-80
WEIGHT (Kg)	600	1160	1640	1900	2580	3060	3980	5610	7820	10000
CLAMPING TO BLADE (T)	135	150	205	250	315	355	500	550	600	705
CLAMPING TO TIP (T)	40	45	65	85	110	120	140	170	205	220