

DEMOLITION AND SORTING GRAB

Demolition and sorting grabs series BS are made with the highest resistant steels, they have been designed for handling of wood, brick and other kind of material.

They have been designed to ensure easy and fast recycling and demolition operations

Due to their particular configuration, selector grabs series BS give the opportunity to operate in limited spaces handling with care.

- Available for excavators from 4 to 120 Tons
- 360° rotation.
- Special balance system to avoid problems during horizontal use
- Different kinds of jaws available (Opened, closed, with grids or with holes)
- Interchangeable blades

MODEL	BS7	BS12	BS16	BS20	BS26	BS32	BS48	BS54	BS70	BS95
OPENING (mm)	1135	1810	2060	2180	2285	2440	2510	3000	3640	3800
LENGTH (mm)	500	700	800	1000	1200	1400	1500	1600	1800	1800
HEIGHT (mm)	840	1300	1400	1500	1500	1550	1600	2300	2650	3000
EXCAVATOR WEIGHT (T)	4-10	8-15	13-19	16-23	21-31	25-50	35-60	45-65	55-80	70-120
WEIGHT (Kg)	365	790	1040	1380	1785	2500	2780	3520	4500	7880
BLADE FORCE (T)	2,5	3,5	5,5	6,5	7,5	10	13	15	17	20
CAPACITY (m³)	0,3	0,5	0,7	0,85	1	1,2	1,4	1,9	2,3	3,5
OIL PRESSURE (BAR)	200	250	300	300	300	300	300	330	340	350
OIL CAPACITY (L/1')	25	50	50	50	50	60	120	150	150	150
OIL ROTATION PRESSURE (BAR)	20	60	60	60	60	60	100	100	100	100
OIL ROTATION CAPACITY (L/1')	2	20	30	30	30	40	40	60	60	60